



SUHNER® COAXIAL CABLE DATA SHEET

TYPE S 02223-02

Single screened coaxial cable - free of halogen

Cable Design



	Material	Detail	Diameter
Centre conductor:	Cu	Wire (0.35 mm)	0.35 mm
Dielectric:	SPE		1.55 mm
1. Outer conductor:	Cu Braid	94% coverage	2 mm
Jacket:	PVC (No print)		2.55 mm +/-0.1

Electrical Data

Impedance:	75 Ω +/-6
Max. operating frequency:	1 GHz
Capacitance :	56 pF / m
Velocity of signal propagation:	0.794285714 %
Signal delay:	4.196642686 ns / m
Min. screening effectiveness:	> 40 dB (up to 1 GHz)
Max. operating voltage:	0.2 kV _{rms} (at sea level)
Test voltage:	0.4 kV _{rms} (50 Hz/ 1min)
Insulation resistance:	> 10 M Ω m

General Data

Temperature range:	-40 °C...+ 85 °C
Weight:	1.1 kg / 100 m
Min. bending radius :	static 15 mm
	repeated (for max. 50 bendings) 25 mm

Suitable Connectors

Cable group **S5 / U2**
(for details refer to the "SUHNER coaxial connector catalogue" or contact you nearest HUBER+SUHNER partner)

Notes

Order as **S 02223-02** under article number **22511275**

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>

Issued: 26.6.2002 15:09

Document: TEMP_PDB_2251127
5.PDF

RF_Co_Ca_PDF

uncontrolled copy

Page 1



SUHNER® COAXIAL CABLE DATA SHEET

TYPE S 02223-02

Matrix Attenuation [formula : (a*f^0.5 +b*f)] and Power CW [formula : (p*/f^0.5)]

Coefficients:

a= 0.616

b= 0.067

f_{max}= 1

p_{at 1GHz} = 33

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0.05	0.141	0.0430	147.6
0.10	0.201	0.0613	104.4
0.15	0.249	0.0759	85.2
0.20	0.289	0.0881	73.8
0.25	0.325	0.0991	66.0
0.30	0.357	0.1088	60.2
0.35	0.388	0.1183	55.8
0.40	0.416	0.1268	52.2
0.45	0.443	0.1350	49.2
0.50	0.469	0.1429	46.7
0.55	0.494	0.1506	44.5
0.60	0.517	0.1576	42.6
0.65	0.540	0.1646	40.9
0.70	0.562	0.1713	39.4
0.75	0.584	0.1780	38.1
0.80	0.605	0.1844	36.9
0.85	0.625	0.1905	35.8
0.90	0.645	0.1966	34.8
0.95	0.664	0.2024	33.9
1.00	0.683	0.2082	33.0

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>

Issued: 26.6.2002 15:09

Document: TEMP_PDB_2251127
5.PDF

RF_Co_Ca_PDF

uncontrolled copy

Page 2