



SUHNER® MICROWAVE CABLE DATA SHEET

TYPE S 04212 B

S-SERIES, the economical low loss microwave cable

Cable Design



	Material	Detail	Diameter
Centre conductor:	CuAg	Wire	1.4 mm
Dielectric:	SPE		3.82 mm
1. Outer conductor:	Al longitudinal Foil	100% coverage	3.96 mm
2. Outer conductor:	CuSn Braid	86% coverage	4.48 mm
Jacket:	PUR	RAL 9005 - bk	5.3 mm
Print:	SUHNER SWITZERLAND S 04212 B 50 Ohm		

Electrical Data

Impedance:	50	Ω
Max. operating frequency:	18	GHz
Capacitance:	82	pF / m
Velocity of signal propagation:	82	%
Signal delay:	4.1	ns / m
Min. screening effectiveness:	> 90	dB (up to 18 GHz)
Max. operating voltage:	0.5	kV _{rms} (at sea level)

General Data

Temperature range:	-40 °C...+ 85 °C
Weight:	4.1 kg / 100 m
Min. bending radius :	static 25 mm
	dynamic 90 mm

Suitable Connectors

Cable group *n/a*
(for details refer to the "SUHNER Microwave Cables and Assemblies General Catalogue" or contact you nearest HUBER+SUHNER partner)

Notes

Order as **S 04212 B** under article number **22511855**

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>

Issued: 5.6.2002 09:19

Document: TEMP_PDB_2251185
5.PDF

RF_Co_Ca_PDF

uncontrolled copy

Page 1



SUHNER® MICROWAVE CABLE DATA SHEET

TYPE S 04212 B

Matrix Attenuation [formula : (a*f^0.5 +b*f)] and Power CW [formula : (p*/f^0.5)]

Coefficients:

a= 0.197

b= 0.045

f_{max}= 18

p_{at 1GHz} = 120

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0.5	0.16	0.049	170
1	0.24	0.073	120
2	0.37	0.113	85
3	0.48	0.146	69
4	0.57	0.174	60
5	0.67	0.204	54
6	0.75	0.229	49
7	0.84	0.256	45
8	0.92	0.280	42
9	1.00	0.305	40
10	1.07	0.326	38
11	1.15	0.351	36
12	1.22	0.372	35
13	1.30	0.396	33
14	1.37	0.418	32
15	1.44	0.439	31
16	1.51	0.460	30
17	1.58	0.482	29
18	1.65	0.503	28

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



HUBER+SUHNER AG

Interconnect Division

CH-9100 Herisau

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

<http://www.hubersuhner.com>

Issued: 5.6.2002 09:19

Document: TEMP_PDB_2251185
5.PDF

RF_Co_Ca_PDF

uncontrolled copy

Page 2